

XtremeFlashing™ Synthetic Butyl Tape

Tech Support / Sales: 800-334-1676
www.tamlyn.com

SECTION 1: PRODUCT IDENTIFICATION

PRODUCT NUMBER: **WSB**

PRODUCT DESCRIPTION: Flashing Tape, Synthetic Butyl

SECTION 2: INGREDIENTS

Based on data available, none of the components in this product are considered hazardous according to OSHA Hazard Communication Standard (29 CFR 1910.1200). The composition of this compound is proprietary information. In the event of a medical emergency, detailed information will be provided to a nurse or physician.

SECTION 3: HAZARD(S) IDENTIFICATION

Emergency Overview

HMIS RATING: HEALTH-0

FLAMMABILITY-0

REACTIVITY-0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

POTENTIAL HEALTH EFFECTS BY ROUTE OF ENTRY:

EYE: No irritation hazard in normal industrial use.

SKIN: No irritation hazard in normal industrial use.

INHALATION: No irritation hazard in normal industrial use. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract. Prolonged exposure may lead to inflammation and ulceration.

INGESTION: Ingestion is not an anticipated route of exposure.

LONG-TERM (CHRONIC) HEALTH EFFECTS

TARGET ORGAN(S): No organs known to be damaged from exposure to this product.

REGULATED CARCINOGEN STATUS:

Unless noted below, this product does not contain regulated levels of NTP, IARC, ACGIH, or OSHA listed carcinogens.

EXISTING HEALTH CONDITIONS AFFECTED BY EXPOSURE: No medical conditions affected by exposure.

SECTION 4: FIRST AID MEASURES

IF IN EYES: This product is an inert solid. Remove the substance from the eye(s), and immediately flush eye(s) with plenty of water while retracting eyelids often. If inflammation or blurred vision develops, seek medical attention and provide the medical care professional with this MSDS.

IF ON SKIN: Wash with soap and water.

IF VAPORS INHALED: Not an anticipated route of exposure. This product is an inert solid. If dusts are produced by cutting or sanding this product, please consider improving work site ventilation.

IF SWALLOWED: No hazard in normal industrial use. Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this MSDS.

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT: Not applicable

AUTOIGNITION TEMPERATURE: Not applicable

LOWER EXPLOSIVE LIMIT (% in air): Not established

UPPER EXPLOSIVE LIMIT (% in air): Not established

EXTINGUISHING MEDIA: Use water spray, foam, dry chemical or carbon dioxide.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Material will burn in a fire.

SPECIAL FIRE FIGHTING INSTRUCTIONS: Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.

HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide, Carbon monoxide, Bromine containing gases

XtremeFlashing™ Synthetic Butyl Tape

Tech Support / Sales: 800-334-1676
www.tamlyn.com

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION: No adverse health effects expected from the clean-up of spilled material. Follow personal protective equipment recommendations found in Section 8 of this MSDS.

SECTION 7: HANDLING AND STORAGE

Handling: No special handling instructions due to toxicity.

Storage: Store in a cool, dry place.

Consult the Technical Data Sheet for specific storage instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION: Wear goggles when handling this product.

SKIN PROTECTION: Protect skin accordingly if working in environments with elevated temperatures.

GLOVES: Not normally required. Use nitrile gloves if conditions warrant.

RESPIRATORY PROTECTION: Not normally required.

VENTILATION: Use local exhaust ventilation to minimize exposure.

HYGIENIC PRACTICES: Wash hands before eating, smoking, or using the restroom.

EXPOSURE LIMITS: None applicable for this product when used for normal industrial applications. Avoid excessive and unnecessary exposure whenever possible. If deemed useful and essential for treatment, specific exposure limits of raw materials used during the manufacturing process will be provided to a nurse or physician.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE:	Solid
COLOR:	Black
ODOR:	Slight
ODOR THRESHOLD:	Not established
SPECIFIC GRAVITY:	1.2 – 1.3
pH:	Not established
BOILING POINT (deg. C):	Not established
FREEZING/MELTING POINT (deg. C):	Not established
VAPOR PRESSURE (mm Hg):	Not established
VAPOR DENSITY:	Not established
EVAPORATION RATE:	Not established
OCTANOL/WATER COEFFICIENT:	Not established

SECTION 10: STABILITY AND REACTIVITY

STABILITY:	Stable under normal conditions
CHEMICAL INCOMPATIBILITY:	Not established
HAZARDOUS POLYMERIZATION:	Will not occur
HAZARDOUS DECOMPOSITION PRODUCTS:	Carbon monoxide, carbon dioxide, Bromine containing gases

XtremeFlashing™ Synthetic Butyl Tape

Tech Support / Sales: 800-334-1676
 www.tamlyn.com

SECTION 11: TOXICOLOGICAL AND EPIDEMIOLOGICAL DATA

CHEMICAL NAME	LD50/LC50
Calcium Carbonate	Oral LD50 Rat=6450 mg/kg
Carbon Black	Oral LD50 Rat > 15400 mg/kg; Dermal LD50 Rabbit > 3 g/kg

TOXICOLOGY SUMMARY: No additional health information available.

SECTION 12: ECOLOGICAL INFORMATION

None available at this time.

SECTION 13: DISPOSAL CONSIDERATIONS

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Dispose of in accordance with federal, state, and local law. Consult your state, local or provincial authorities and your local waste vendor for more restrictive requirements.

SECTION 14: TRANSPORT INFORMATION

Consult Bill of Lading for transportation information.

SECTION 15: REGULATORY INFORMATION

INVENTORY STATUS:

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's inventory requirements.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others).

FEDERAL REPORTING:

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 72. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

CHEMICAL NAME	CAS#	WT%*
Isobutylene Copolymer	9010-85-9	10-40
Polyisobutylene	9003-27-4	10-40
Calcium Carbonate	471-34-1	15-45
Carbon Black	1333-86-4	<5
Polyethylene	9002-88-4	<15

*-Proprietary blend

CANADIAN WHMIS STATUS: To the best of our knowledge, this material is classified as a NONCONTROLLED PRODUCT.

XtremeFlashing™ Synthetic Butyl Tape

Tech Support / Sales: 800-334-1676
www.tamlyn.com

SECTION 16: ADDITIONAL INFORMATION

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200). The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to **TAMLYN** from its suppliers, and because **TAMLYN** has no control over the conditions of handling and use, **TAMLYN** makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and **TAMLYN** assumes no responsibility for use or reliance thereon. It is the responsibility of the user of **TAMLYN** products to comply with all applicable federal, state and local laws and regulations.